2012 Emissions Inventory Report

WILLIAMSBURG MANUFACTURING (48-02-009)

FACILITY Identifier:

48-02-009

Facility Name:

WILLIAMSBURG MANUFACTURING

Company/Owner Name:

COSMA BODY SYSTEMS

Description:

Williams burg Manufacturing, a subsidiary of Magna Corporation, is a supplier of vehicle parts (e.g. bumpers, radiator support frames) for major automobile and light truck manufacturers. Processes at

the facility include metal cleaning, machining, stamping, shaping and welding.

Status: ONRE - Operating as Minor Source

Status Date:

Category:

UNK - Facility category per 40 CFR 70 Major Source definitions is unknown.

NAICS:

336370 - Motor Vehicle Metal Stamping

Comments:

| FACILITY - CONTACTS |
|---------------------|
| Emissions Contact: |

Email KDALE@COSMA.COM

Other 408 MAPLEWOOD AVE WILLIAWSBURG, IA 52361

KURT DALE

Other PO BOX 808 WILLIAMSBURG,IA 52361

Phone (319) 668-8589

FACILITY - ADDRESSES

Location Address:

408 MAPLEWOOD AVE WILLIAMSBURG, IA 52361

Mailing Address:

PO BOX 808

WILLIAMSBURG, IA52361

FACILITY - LOCATION

Latitude (decimal degress):

41.66303 583395

Longitude (decimal degress):

-91.99830

UTM X (meters):

UTM Y (meters):

4612849

UTM Zone:

15

Collection Method:

014 - GPS code measurements (pseudo range) differential (DGPS)

Data Collection Date:

Geographic Reference Point:

101 - Entrance Point of a Facility, System, or

Station

Geodetic Reference System:

002 - North American Datum of 1983

FACILITY - ADDITIONAL INFORMATION

| Field Name | Field Value |
|-----------------|-------------|
| Interest Type | MINOR EI |
| Map Scale No | 0 |
| Secondary NAICS | 332812 |

| RELEASE POIN | пѕ | | | | |
|--------------|---------------------------|-------------------------------------------------------------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| ID | Туре | Description | Status | Details | Location |
| ₽-16 | Vertical | SOUTHWELDLINESTACK | ОР | Height: 44.5 FEET, Shape: Orcular, Diameter: 4.0 FEET, Temperature: 68.0F, Flow Rate: 36,000.0 SCFM Velocity: , Fenceline Distance: 175.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Exit Temp Ambient Flag: Y, Rain Cap Flag: N | |
| E -17 | Vertical | MDDLEWELD LINESTACK | OP | Height: 42.0 FEET, Shape: Circular, Diameter: 2.0 FEET, Temperature: 70.0F, Flow Rate: 28,000.0 SCFM, Velocity: , Fenceline Distance: 148.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | |
| ₽-18 | Vertical | NE RADIATOR SUPPORT LINE STACK | OP | Height: 40.0 FEET, Shape: Orcular, Diameter: 3.33 FEET, Temperature: 70.0F, Flow Rate: 28,000.0 SCFM, Velocity: , Fenceline Distance: 415.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | |
| EP-19 | Vertical | SERADIATOR SUPPORT LINESTACK | OP | Height: 40.0 FEET, Shape: Circular, Diameter: 3.33 FEET, Temperature: 70.0F, Flow Rate: 19,000.0 SCFM, Velocity: , Fenceline Distance: 415.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | |
| EP-20 | Vertical | NW RADIATOR SUPPORT LINE STACK | OP | Height: 40.0 FEET, Shape: Orcular, Diameter: 3.33 FEET, Temperature: 70.0F, Row Rate: 28,000.0 SOFM Velocity: , Fenceline Distance: 394.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | |
| ₽ 21 | Vertical | SW RADIATOR SUPPORT LINE STACK | OP | Height: 40.0 FEET, Shape: Orcular, Diameter: 3.33 FEET, Temperature: 68.0F, Flow Rate: 28,000.0 SCFM Velocity: , Fenceline Distance: 394.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Exit Temp Ambient Flag: Y, Rain Cap Flag: N | |
| EP-24 | Vertical | NORTH WELDING LINE STACK | OP | Height: 40.0 FEET, Shape: Circular, Diameter: 2.0 FEET, Temperature: 70.0F, Flow Rate: 28,000.0 SCFM, Velocity: , Fenceline Distance: 175.0 FEET | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | |
| EP-31 | Fugitive | DRILL LINES EMISSIONS | OP | Fugitive Height: , Fugitive Width: , Fugitive Length: , Fugitive Angle: | Lat/Long: (41.66303, -91.99830), UTM X/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Exit Temp Ambient Flag: Y, Fugitiv | ve or Other Type T | ext: VENTS INSIDE BUILDING | |
| ⊞ -32 | Fugitive | TIG WELDING EMISSIONS | OP | Fugitive Height: , Fugitive Width: , Fugitive Length: , Fugitive Angle: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Exit Temp Ambient Flag: Y, Fugitiv | ve or Other Type T | ext: VENTS INSIDE BUILDING | |
| EP-33 | Vertical with Rain Cap | E-COAT DIPTANK STACK | OP | Height: 33.0 FEET, Shape: Circular, Diameter: 1.5 FEET, Temperature: 70.0F, Row Rate: 3,620.0 SCFM, Velocity: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: VR - Verti | cal, with obstructin | ng rain cap, or horizontal discharge, Rain Cap Flag: Y, Rain Cap Text: RAIN C | AP . |
| EP-34 | Vertical | PAINT PLANT CURE OVEN ZONE 2 STACK | OP | Height: 33.5 FEET, Shape: Circular, Diameter: 2.83 FEET, Temperature: 240.0F, Flow Rate: 13,500.0 SCRM, Velocity: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | T |
| EP-35 | Vertical | PAINT CURE OVEN ZONE 3 STACK | OP | Height: 33.5 FEET, Shape: Circular, Diameter: 2.83 FEET, Temperature: 240.0F, Flow Rate: 14,200.0 SCRM, Velocity: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | al, without rain cap | or with unobstructing rain cap, Rain Cap Flag: N | |

| ID | Туре | Description | Status | Details | Location |
|--------------|-----------------|------------------------------------------------------------|-----------------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| ₽ -4 | Vertical | PAINT HOOK PYROLIZER | OP | Height: 29.3 FEET, Shape: Circular, Diameter: 1.33 FEET, Temperature: 1,250.0F, Flow Rate: 1,380.0 SCFM, Velocity: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | l, without rain cap o | or with unobstructing rain cap, Rain Cap Flag: N | |
| EP-42 | Fugitive | 7166/7197 STEERING COLUMN WELDING EMISSIONS | OP | Fugitive Height: , Fugitive Width: , Fugitive Length: , Fugitive Angle: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Fugitive or Other Type Text: VEN | S INSIDE BUILDING | | |
| ₽-48 | Fugitive | C-SEGMENT B-PILLAR WELDING SYSTEM EMISSIONS | OP | Fugitive Height: , Fugitive Width: , Fugitive Length: , Fugitive Angle: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Fugitive or Other Type Text: VEN | S INSIDE BUILDING | | |
| EP-49 | Fugitive | C-SEGMENT UPPER DASH CROSS MEMBER WELDING SYSTEM | OP | Fugitive Height: , Fugitive Width: , Fugitive Length: , Fugitive Angle: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Fugitive or Other Type Text: VEN | S INSIDE BUILDING | | |
| ₽ -50 | Fugitive | COWL PLENUM WELDING SYSTEM EMISSIONS | OP | Fugitive Height: , Fugitive Width: , Fugitive Length: , Fugitive Angle: | Lat/Long: (41.66303, -91.99830), UTM X/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Fugitive or Other Type Text: VEN | S INSIDE BUILDING | | |
| EP-54 | Vertical | SOUTH WELDING LINE NO.2 | OP | Height: 29.0 F⊞T, Shape: Circular, Diameter: 2.0 F⊞T, Temperature: 68.0F, Flow Rate: 17,532.0 SCFM, Velocity: | Lat/Long: (41.66303, -91.99830), UTMX/Y/Z: (583395, 4612849, 15) |
| | Additional Info | rmation: Bypass Flag: N, Discharge Style Type: V - Vertica | l, without rain cap o | or with unobstructing rain cap, Exit Temp Ambient Flag: Y, Rain Cap Flag: N | |
| EP-59 | Uhknown | FRONT CRADLE WAX COATING | OP | Height: , Shape: Circular, Diameter: , Temperature: F, Flow Rate: , Velocity: | Lat/Long: , UTM X/Y/Z: |
| | Additional Info | rmation: Bypass Flag: N | | | |
| EP-60 | Unknown | REAR CRADLE WAX COATING | OP | Height: , Shape: Circular, Diameter: , Temperature: F, Flow Rate: , Velocity: | Lat/Long: , UTMX/Y/Z: |
| | Additional Info | rmation: Bypass Flag: N | | | |

| CONTROL DEVICE | CONTROL DEVICES | | | | | | |
|----------------|---------------------------|--------|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| ID | Description | Status | Control Measure | Controlled Pollutants | | | |
| OE-36 | PYROLIZER AFTERBURNER | OP | 112 - Afterburner | PM25-PRI-PM2.5 Primary (Filt + Cond): 70.0%, PM10-PRI-PM10 Primary (Filt + Cond): 70.0%, VOC-Volatile Organic Compounds: 95.0%, CO-Carbon Monoxide: 95.0% | | | |
| Œ-49 | CARTRIDGE MIST BLIMINATOR | OP | 211 - Mist Birninator | PM25-PRI-PM2.5 Primary (Filt + Cond): 90.0%, PM10-PRI-PM10 Primary (Filt + Cond): 90.0% | | | |
| Œ-50 | CARTRIDGE MIST BLIMINATOR | OP | 211 - Mist Birninator | PM25-PRI-PM2.5 Primary (Filt + Cond): 90.0%, PM10-PRI-PM10 Primary (Filt + Cond): 90.0% | | | |
| Œ-59 | DRY OVERSPRAY FILTERS | OP | 99 - Other Control Device | PM25-PRI-PM2.5 Primary (Filt + Cond): 95.0%, PM10-PRI-PM10 Primary (Filt + Cond): 95.0% | | | |
| Œ-60 | DRY OVERSPRAY FILTERS | OP | 99 - Other Control Device | PM25-PRI-PM2.5 Primary (Filt + Cond): 95.0%, PM10-PRI-PM10 Primary (Filt + Cond): 95.0% | | | |

| EMISSION U | NITS | | | | | | | |
|------------|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------|--|--|--|--|
| ID | Туре | Description | Status | Details | | | | |
| PO1 | 450 - Spray Booth or Coating Line | ELECTROCOATING DIP TANK | OP | Operation Start: , Design Capacity: | | | | |
| PO2 | 999 - Unclassified | PAINT PLANT CUREOVEN ZONE 2 | OP | Operation Start: , Design Capacity: 12.0E6BTU/HR | | | | |
| | Additional Information: Construction Date: 06/01/1997, | Construction Limits Desc: Other: Reduced allowable emission | n rate of 0.01 gr/sc | f | | | | |
| PO3 | 999 - Unclassified | PAINT PLANT CURE OVEN JONE 1 | OP | Operation Start: , Design Capacity: 7.69E6BTU/HR | | | | |
| | Additional Information: Construction Date: 06/01/1997, | Construction Limits Desc: Other: Reduced allowable emission | n rate of 0.01 gr/sc | f | | | | |
| PO4 | 270 - Incinerator | BAKE OVENPAINT HOOK | OP | Operation Start: , Design Capacity: | | | | |
| PO5 | 100 - Boiler | PAINT PLANT HOT WATER HEATER | OP | Operation Start: , Design Capacity: 15.0E6BTU/HR | | | | |
| | Additional Information: Construction Date: 06/01/1997, | Construction Limits Desc: Other: Reduced allowable emission | n rate of 0.01 gr/sc | f | | | | |
| EJ-2 | 999 - Unclassified | AIRHEATER | PS on 08/03/2007 | Operation Start: , Design Capacity: 0.00158MMOF/HR | | | | |
| | Additional Information: Construction Date: 01/01/1980, | Federal Enforceable Limit Text: .37 LBS/HR PW-10, Installatio | n Date: 01/01/1980, | Permit or Rule Limit Text: 96-A-207-R | | | | |
| EU-5 | 100 - Boiler | AGING OVEN BURNER EXHAUST | PS on 11/05/2004 | Operation Start: , Design Capacity: 0.0023MMOF/HR | | | | |
| | Additional Information: Construction Date: 01/01/1980, | Federal Enforceable Limit Text: PM-10 0.83 LB/HR,0.1GR/SC | F, Installation Date: | 01/01/1980, Permit or Rule Limit Text: 96-A-202-R | | | | |
| EU-6 | 100 - Boiler | HEAT TREAT BURNER EXHAUST | PS on 11/05/2004 | Operation Start: , Design Capacity: 0.00238MMOF/HR | | | | |
| | Additional Information: Construction Date: 01/01/1980, | Federal Enforceable Limit Text: PM-10: 039LB/HR/0.1GR/SCF | , Installation Date: 0 | 01/01/1980, Permit or Rule Limit Text: 96-A-208-R | | | | |
| EU-9 | 100 - Boiler | HEAT TREAT TANK HEATER | PS on 11/05/2004 | Operation Start: , Design Capacity: 0.00048MMCF/HR | | | | |
| | Additional Information: Construction Date: 01/01/1980, | Installation Date: 01/01/1980, Permit or Rule Limit Text: 96-A- | 209-R | | | | | |
| EJ-16 | 999 - Unclassified | 21 ROBOT WELDERS AND 6 PROJECTION WELDERS | OP | Operation Start: , Design Capacity: 10.0 | | | | |
| | Additional Information: Construction Date: 01/01/1985, LBS/HR PM-10, Installation Date: 01/01/1985, Modification | | rate of 0.004 gr/so | cf. *The combined welding wire usage may not exceed 90 lbs/hr, Federal Enforceable Limit Text: 0.08 | | | | |
| EJ-17 | 999 - Unclassified | 21 ROBOT WELDERS | OP | Operation Start: , Design Capacity: 10.0 | | | | |
| | Additional Information: Construction Date: 01/01/1985, 03/01/2005, Permit or Rule Limit Text: 96-A-211-S3 | Construction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/so | cf., Federal Enforceable Limit Text: 1.04 LBS/HR PM-10, Installation Date: 01/01/1985, Modification Date: | | | | |
| EU-18 | 999 - Unclassified | 25 ROBOT WELDERS | OP | Operation Start: , Design Capacity: 25.0 | | | | |
| | Additional Information: Construction Date: 01/01/1996, 03/11/2003, Permit or Rule Limit Text: 96-A-1082-S2 | Construction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/so | cf., Federal Enforceable Limit Text: 0.96 LBS/HR PM-10, Installation Date: 01/01/1996, Modification Date: | | | | |
| EJ-19 | 999 - Unclassified | 8 ROBOT WELDERS | OP | Operation Start: , Design Capacity: 8.0 | | | | |
| | Additional Information: Construction Date: 01/01/1997, 03/11/2003, Permit or Rule Limit Text: 96-A-1083-S2 | Additional Information: Construction Date: 01/01/1997, Construction Limits Desc: Other: reduced allowable emission rate of 0.004 gr/scf., Federal Enforceable Limit Text: .65 LBS/HR PM-10, Installation Date: 01/01/1997, Modification Date: 03/11/2003, Permit or Rule Limit Text: 96-A-1083-S2 | | | | | | |
| EJ-20 | 999 - Unclassified | MAZDA REAR CRADLE WELDING LINE | OP | Operation Start: , Design Capacity: 26.0 | | | | |
| | Additional Information: Construction Date: 01/01/1997, LBS/HR PM-10, Installation Date: 01/01/1997, Modification | | rate of 0.004 gr/so | cf. *The combined welding wire usage may not exceed 170 lbs/hr, Federal Enforceable Limit Text: .96 | | | | |
| EJ-21 | 999 - Unclassified | MAZDA FRONT CRADLE WELDING LINE | OP | Operation Start: , Design Capacity: 13.0 | | | | |
| | Additional Information: Construction Date: 01/01/1997, LBS/HR PM-10, Installation Date: 01/01/1997, Modification | | rate of 0.004 gr/so | cf. *The combined welding wire usage may not exceed 170 lbs/hr, Federal Enforceable Limit Text: 0.49 | | | | |

| ID | Туре | Description | Status | Details | | | | | |
|-------|-----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----------------------------------------------------------------------------------------------------------|--|--|--|--|--|
| EJ-22 | 999 - Unclassified | UPPER TIE BAR WELDING (SOUTH) | PS on 08/03/2007 | Operation Start: , Design Capacity: 4.0 | | | | | |
| | Additional Information: Construction Date: 01/01/1996, Oct Rule Limit Text: 96-A-1086-S4-R | Additional Information: Construction Date: 01/01/1996, Construction Limits Desc: Other: reduced allowable emission rate of 0.004 gr/scf., Federal Enforceable Limit Text: 0.12LB/HR PM-10/0.1GR/SCFT2, Installation Date: 01/01/1997, Permit or Rule Limit Text: 96-A-1086-S4-R | | | | | | | |
| EJ-23 | 999 - Unclassified | 8 ROBOT WELDERS | PS on 05/09/2008 | Operation Start: , Design Capacity: 8.0 | | | | | |
| | Additional Information: Construction Date: 01/01/1999, Oc 03/11/2003, Permit or Rule Limit Text: 98-A-816-S2-R | nstruction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/sct | f., Federal Enforceable Limit Text: .65 LBS/HR PM-10, Installation Date: 01/01/1999, Modification Date: | | | | | |
| EU-24 | 999 - Unclassified | 21 ROBOT WELDERS | OP | Operation Start: , Design Capacity: 10.0 | | | | | |
| | Additional Information: Construction Date: 01/01/1985, Oc 03/01/2005, Permit or Rule Limit Text: 98-A-817-S2 | nstruction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/sct | f., Federal Enforceable Limit Text: 1.10 LBS/HR PM-10, Installation Date: 01/01/1985, Modification Date: | | | | | |
| EJ-25 | 999 - Unclassified | 12 ROBOT WELDERS | PS on 05/09/2008 | Operation Start: , Design Capacity: 12.0 | | | | | |
| | Additional Information: Construction Date: 03/01/2000, Oc 03/11/2003, Permit or Rule Limit Text: 99-A-1045-S2-R | nstruction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/sct | f., Federal Enforceable Limit Text: .65 LBS/HR PM-10, Installation Date: 03/01/2000, Modification Date: | | | | | |
| EJ-26 | 999 - Unclassified | 12 ROBOT WELDERS | PS on 08/03/2007 | Operation Start: , Design Capacity: 12.0 | | | | | |
| | Additional Information: Construction Date: 03/01/2000, Oc 03/11/2003, Permit or Rule Limit Text: 99-A-1046-S1-R | nstruction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/sct | f., Federal Enforceable Limit Text: .65 LBS/HR PM-10, Installation Date: 03/01/2000, Modification Date: | | | | | |
| EJ-27 | 999 - Unclassified | 27 ROBOT WELDERS | PS on 08/03/2007 | Operation Start: , Design Capacity: 30.0 | | | | | |
| | Additional Information: Construction Date: 03/01/2000, Oc 03/11/2003, Permit or Rule Limit Text: 99-A-1047-S1-R | nstruction Limits Desc: Other: reduced allowable emission | rate of 0.004 gr/sct | f., Federal Enforceable Limit Text: 1.20 LBS/HR PM-10, Installation Date: 03/01/2000, Modification Date: | | | | | |
| EU-28 | 999 - Unclassified | 9069 SPOT WELDING SYSTEM | OP | Operation Start: , Design Capacity: 1,200.0EACH/HR | | | | | |
| | Additional Information: Construction Date: 01/01/1995, Ins | stallation Date: 01/01/1995 | | | | | | | |
| EU-29 | 999 - Unclassified | A098/A099 SAWING AND MILLING EQUIPMENT | OP | Operation Start: , Design Capacity: 0.005TOWHR | | | | | |
| | Additional Information: Construction Date: 01/01/1997, Ins | stallation Date: 01/01/1997 | | | | | | | |
| EU-30 | 999 - Unclassified | WELD GRINDING STATIONS | OP | Operation Start: , Design Capacity: 0.00255TOWHR | | | | | |
| | Additional Information: Construction Date: 01/01/1997, Ins | stallation Date: 01/01/1997 | | | | | | | |
| EU-31 | 999 - Unclassified | DRILL LINES | OP | Operation Start: , Design Capacity: 0.01TON/HR | | | | | |
| | Additional Information: Construction Date: 01/01/1997, Ins | stallation Date: 01/01/1997, Permit or Rule Limit Text: SUE | • | | | | | | |
| EU-32 | 999 - Unclassified | TIGWELDERS | OP | Operation Start: , Design Capacity: 0.003E3LB/HR | | | | | |
| | Additional Information: Construction Date: 01/01/1997, Ins | stallation Date: 01/01/1997, Permit or Rule Limit Text: SUE | | | | | | | |
| EU-33 | 450 - Spray Booth or Coating Line | E-COAT DIPTANK | OP | Operation Start: , Design Capacity: 7.29GAL/HR | | | | | |
| | Additional Information: Construction Date: 01/01/1997, Ins | stallation Date: 01/01/1997, Permit or Rule Limit Text: 97-A-5 | 02 | | | | | | |
| EJ-34 | 290 - Other combustion | PAINT PLANT CURE OVEN ZONE 2 | OP | Operation Start: , Design Capacity: 0.0095MMOF/HR | | | | | |
| | Additional Information: Construction Date: 05/20/1997, Fe | deral Enforceable Limit Text: 1.16 LBS/HR PM-10, Installatio | n Date: 10/07/1997 | , Modification Date: 10/29/2003, Permit or Rule Limit Text: 97-A-503-S2 | | | | | |
| EJ-35 | 290 - Other combustion | PAINT CURE OVEN ZONE 3 | OP | Operation Start: , Design Capacity: 0.0095M/ICF/HR | | | | | |
| | Additional Information: Construction Date: 05/20/1997, Fe | deral Enforceable Limit Text: 1.40 LBS/HR PM-10, Installatio | n Date: 10/01/1997 | , Modification Date: 10/29/2003, Permit or Rule Limit Text: 97-A-504-S2 | | | | | |

| ID | Туре | Description | Status | Details |
|--------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------|
| EU-36 | 290 - Other combustion | PAINT HOOK PYROLIZER | OP | Operation Start: , Design Capacity: 0.0003MVOF/HR |
| | Additional Information: Construction Date: 01/01/1992, Fe | deral Enforceable Limit Text: 1.18 LB/HR PM10, Installation | Date: 01/01/1999, N | /bdification Date: 03/07/2000, Permit or Rule Limit Text: 99-A-148-S2 |
| EJ-37 | 999 - Unclassified | BRYAN HOT WATER HEATER | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 01/01/1997, Co 10/29/2003, Permit or Rule Limit Text: 03-A-1119 | onstruction Limits Desc: *Only natural gas may be burned in | the water heater, | Federal Enforceable Limit Text: .30 LBS/HR PM-10, Installation Date: 01/01/1997, Modification Date: |
| EJ-38 | 999 - Unclassified | NSSAN FUEL BOX WELD SYSTEM | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 01/01/2005, Ins | stallation Date: 01/01/2005 | | |
| EJ-39 | 999 - Unclassified | 4L46 FUEL BOX WELD SYSTEM | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 03/01/2005, Ins | stallation Date: 03/01/2005 | | |
| EU-41 | 999 - Unclassified | P221 WELD HEAD | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 03/01/2005, Ins | stallation Date: 03/01/2005 | | |
| EU-42 | 999 - Unclassified | 7166/7197 STEERING COLUMN WELDER | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 03/01/2005, Ins | stallation Date: 03/01/2005, Permit or Rule Limit Text: SUE | • | |
| EU-48 | 999 - Unclassified | C-SEGMENT B-PILLAR WELDING SYSTEM | OP | Operation Start: , Design Capacity: |
| | Additional Information: Permit or Rule Limit Text: SUE | | | |
| EU-49 | 999 - Unclassified | C-SEGMENT UPPER DASH CROSS MEMBER WELD SYSTEM | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 03/01/2005, Ins | stallation Date: 03/01/2005, Permit or Rule Limit Text: SUE | | |
| EJ-50 | 999 - Unclassified | COWL PLENUM WELDING SYSTEM | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 03/01/2005, Ins | stallation Date: 03/01/2005, Permit or Rule Limit Text: SUE | | |
| EU-53 | 999 - Unclassified | ENFN INDUCTION WELDING SYSTEM | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 03/01/2005, Ins | stallation Date: 03/01/2005 | | |
| EU-54 | 999 - Unclassified | SOUTH WELDING LINE NO.2 | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 09/01/2007, Fe | deral Enforceable Limit Text: 0.4 LB/HR PM10, Installation D | ate: 09/01/2007, M | odification Date: 12/03/2008, Permit or Rule Limit Text: 07-A-1087-S2 |
| EU-57 | 999 - Unclassified | 3910/3911 SPOT WELDING | OP | Operation Start: , Design Capacity: |
| EJ-58 | 999 - Unclassified | UPPER TIE BAR SPOT WELDING | OP | Operation Start: , Design Capacity: |
| EU-59 | 450 - Spray Booth or Coating Line | FRONT CRADLE WAX COATING | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 01/01/2011, Ins | stallation Date: 01/01/2011, Permit or Rule Limit Text: SUE | | |
| EU-60 | 450 - Spray Booth or Coating Line | REAR CRADLE WAX COATING | OP | Operation Start: , Design Capacity: |
| | Additional Information: Construction Date: 01/01/2011, Ins | stallation Date: 01/01/2011, Permit or Rule Limit Text: SUE | | |
| EU-22A | 999 - Unclassified | 4 ROBOT WELDERS | PS on 08/03/2007 | Operation Start: , Design Capacity: 4.0 |
| | Additional Information: Construction Date: 01/01/1997, Co Modification Date: 03/11/2003, Permit or Rule Limit Text: 96-A | | allowable emission | rate 0.004 gr/scf., Federal Enforceable Limit Text: .30 LBS/HR PM-10, Installation Date: 01/01/1997, |
| EU-22B | 999 - Unclassified | 8 INDUCTION SPOT WELDERS | PS on 08/03/2007 | Operation Start: , Design Capacity: 8.0 |

| ID | Туре | Description | Status | Details | | | | |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|--------|-----------------------------------------------|--|--|--|--|
| | Additional Information: Construction Date: 10/31/2004, Construction Limits Desc: Other: existing permit has reduced allowable emission rate of 0.004 gr/scf., Federal Enforceable Limit Text: .30 LBS/HR PM-10, Installation Date: 10/31/2004, Permit or Rule Limit Text: 96-A-1086-S4-R | | | | | | | |
| EJ-36B | 270 - Incinerator | PAINT HOOK PYROLIZER | OP | Operation Start: , Design Capacity: 10.0LB/HR | | | | |
| | Additional Information: Construction Date: 01/01/1990, Federal Enforceable Limit Text: 0.35 LP PW/HR, Installation Date: 01/01/1990, Modification Date: 03/07/2000, Permit or Rule Limit Text: 99-A-148-S1 | | | | | | | |
| EJ-55 A-D | 999 - Unclassified | INFINIA POST ASSEMBLY WELDING SYSTEM | OP | Operation Start: , Design Capacity: | | | | |
| | Additional Information: Construction Date: 02/15/2009, Permit or Rule Limit Text: 09-A-042 | | | | | | | |
| EJ-56 A-H | 999 - Unclassified | INFINIA BOOMARMWELDING LINE | OP | Operation Start: , Design Capacity: | | | | |
| | Additional Information: Construction Date: 02/15/2009, Pe | Additional Information: Construction Date: 02/15/2009, Permit or Rule Limit Text: 09-A-043 | | | | | | |

| UNIT PROCESSES | | | | | | | | |
|-------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| EUID | UPID | SCC | Description | Final Year | Details | | | |
| EU-16 21 ROBOT WELDERS AND 6 PROJECTION WELDERS | EJ-16-1 | 30905254 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-16-SOUTH WELD LINE STACK: 100.0% | | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.004, Max Design Rate Unit Code | e: 1000 POUNDS, Raw I | Material Desc: WELDING WIRE | | | |
| EJ-17 21 ROBOT WELDERS | EJ-17 -1 | 30905254 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-17-MDDLE WELD LINE STACK: 100.0% | | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.16, Max Design Rate Unit Code: | : 1000 POUNDS, Raw M | teterial Desc: WELDING WIRE | | | |
| EJ-18 25 ROBOT WELDERS | EJ-18 -1 | 30905226 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-18-NERADIATOR SUPPORT LINE STACK: 100.0% | | | |
| | l | Additional Information: Max Design Rate Amount: 0.04, Max Design Rate Unit Code: 1000 POUNDS, Raw Material Desc: WELDING WIRE | | | | | | |
| EJ-19 8 ROBOT WELDERS | EJ-19 -1 | 30905226 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-19-SERADIATOR SUPPORT LINE STACK: 100.0% | | | |
| | | Additional Informat | Additional Information: Max Design Rate Amount: 0.027, Max Design Rate Unit Code: 1000 POUNDS, Raw Material Desc: WELDING WIRE | | | | | |
| EJ-20 MAZDA REAR CRADLEWELDING LINE | EJ-20 -1 | 30905226 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-20-NW RADIATOR SUPPORT LINE STACK: 100.0% | | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.017, Max Design Rate Unit Code | e: 1000 POUNDS, Raw I | Material Desc: WELDING WIRE | | | |
| EJ-21 MAZDA FRONT CRADLE WELDING LINE | BJ-21 -1 | 30905226 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-21-SW RADIATOR SUPPORT LINE STACK: 100.0% | | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.025, Max Design Rate Unit Code | e: 1000 POUNDS, Raw I | Waterial Desc: WELDING WIRE | | | |

| EUID | UPID | scc | Description | Final Year | Details | | |
|------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| EU-24 21 ROBOT WELDERS | EJ-24 -1 | 30905254 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: B-24-NORTH WELDING LINE STACK: 100.0% | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.212, Max Design Rate Unit Code | e: 1000 POUNDS, Raw N | vaterial Desc: WELDING WIRE | | |
| EU-31 DRILL LINES | EJ-31 -1 | 30903099 | DRILLING METAL PARTS | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-31-DRILL LINES EMSSIONS: 100.0% | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.237, Max Design Rate Unit Code | e: TONS, Raw Material D | Desc: METAL PARTS | | |
| EJ-32 TIG WELDERS | BJ-32 -1 | 30905226 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-32-TIG WELDING EMSSIONS: 100.0% | | |
| | | Additional Information: Max Design Rate Amount: 0.0001, Max Design Rate Unit Code: 1000 POUNDS, Raw Material Desc: TIG WELDING | | | | | |
| EU-33 E-COAT DIPTANK | EJ-33 -1 | 40202532 | DIP COATING PARTS | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-33-E-COAT DIP TANK STACK: 100.0% | | |
| | | Additional Informat | ion: Max Design Rate Amount: 7.29, Max Design Rate Unit Code: | GALLONS, Raw Materia | al Desc: PAINT | | |
| EU-34 PAINT PLANT CURE OVEN ZONE 2 | EJ-34 -1 | 40200801 | NATURAL GAS COMBUSTION | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-34-PAINT PLANT CURE OVEN ZONE 2 STACK: 100.0% | | |
| | 1 | Additional Informat | ion: Max Design Rate Amount: 0.0114, Max Design Rate Unit Cox | de: MILLION CUBIC FEET | , Raw Material Desc: NATURAL GAS | | |
| EU-35 PAINT CURE OVEN ZONE 3 | BJ-35 -1 | 40200801 | NATURAL GAS COMBUSTION | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-35-PAINT CURE OVEN ZONE 3 STACK: 100.0% | | |
| | | Additional Informat | ion: Max Design Rate Amount: 0.00732, Max Design Rate Unit Co | ode: MILLION CUBIC FEE | T, Raw Material Desc: NATURAL GAS | | |

| EUID | UPID | SCC | Description | Final Year | Details | | | |
|-----------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| BU-36 PAINT HOOK PYROLIZER | EJ-36 -1 | 40200801 | NATURAL GAS COMBUSTION | | Control Approach Controlled?: Yes Description: PYROLIZER AFTERBURNER Control Devices: CE-36-PYROLIZER AFTERBURNER Release Point Apportionment: EP-4 -PAINT HOCK PYROLIZER 100.0% | | | |
| | | Additional Informati | on: Max Design Rate Amount: 0.00033, Max Design Rate Unit Co | ode: MILLION CUBIC FEE | T, Raw Material Desc: NATURAL GAS | | | |
| EU-36 PAINT HOOK PYROLIZER | EJ-36 -2 | 49090013 | BURNING PAINT OFF HOOKS | | Control Approach Controlled?: Yes Description: PYROLIZER AFTERBURNER Control Devices: CE-36-PYROLIZER AFTERBURNER Release Point Apportionment: EP-4-PAINT HOOK PYROLIZER 100.0% | | | |
| | | Additional Information: Max Design Rate Amount: 10, Max Design Rate Unit Code: POUNDS, Raw Material Desc: PAINT ASH | | | | | | |
| EU-42 7166/7197 STEERING COLLUMN WELDER | EJ-42 -1 | 30905254 | GAS METAL ARC WELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-42-7166/7197 STEERING COLUMN WELDING EMSSIONS: 100.0% | | | |
| | | Additional Information: Max Design Rate Amount: 0.0005, Max Design Rate Unit Code: 1000 POUNDS, Raw Material Desc: WELDING WIRE | | | | | | |
| EL-48 C-SEGMENT B- PILLAR WELDING SYSTEM | EJ-48 -1 | 30904100 | RESISTANCEWELDING | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-48-C-SEGMENT B-PILLAR WELDING SYSTEM EMISSIONS: 100.0% | | | |
| | | Additional Informati | on: Max Design Rate Amount: 1, Max Design Rate Unit Code: HC | DURS, Raw Material Des | c: METAL PART | | | |
| EU-49 C-SEGMENT UPPER DASH CROSS MEMBER WELD SYSTEM | EJ-49 -1 | 30904100 | RESISTANCEWELDING | | Control Approach Controlled?: Yes Description: CARTIRIDGE MIST ELIMINATOR Control Devices: CE-49-CARTIRIDGE MIST ELIMINATOR Release Point Apportionment: EP-49-C-SEGMENT UPPER DASH CROSS MEMBER WELDING SYSTEM: 100.0% | | | |
| | | Additional Informati | Additional Information: Max Design Rate Amount: 1, Max Design Rate Unit Code: HOURS, Raw Material Desc: METAL PART | | | | | |

| BUID | UPID | SCC | Description | Final Year | Details |
|----------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------|--------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EJ-50 COWL PLENUM WELDING SYSTEM | EU-50 -1 | 30904100 | RESISTANCE WELDING | | Control Approach Controlled?: Yes Description: CARTIRIDGE MIST ELIMINATOR Control Devices: CE-50-CARTIRIDGE MIST ELIMINATOR Release Point Apportionment: EP-50-COWL FLENUMWELDING SYSTEM EMISSIONS: 100.0% |
| | | Additional Information: Max Design Rate Amount: 1, Max Design Rate Unit Code: HOURS, Raw Material Desc: METAL PART | | | |
| EJ-54 SOUTHWELDING LINENO.2 | EU-54 -1 | 30905254 | E70S WELDING WIRE | | Control Approach Controlled?: Yes Description: Control Devices: None Release Point Apportionment: EP-54-SOUTH WELDING LINE NO.2: 100.0% |
| | | Additional Information: Max Design Rate Amount: 0.028, Max Design Rate Unit Code: 1000 POUNDS, Raw Material Desc: WELDING WIRE | | | |
| EU-59 FRONT CRADLE WAX COATING | EU-59 -1 | 40202501 | WAX COATING | | Control Approach Controlled?: Yes Description: DRY OVENSIFRAY FILTERS Control Devices: CE-59-DRY OVENSIFRAY FILTERS Release Point Apportionment: EP-59-FRONT CRADLE WAX COATING: 100.0% |
| | | Additional Information: Max Design Rate Amount: 1, Max Design Rate Unit Code: HOURS, Raw Material Desc: WAX | | | |
| ELF60 REAR CRADLE WAX COATING | EU-60 -1 | 40202501 | WAX COATING | | Control Approach Controlled?: Yes Description: DRY OVENSIFRAY FILTERS Control Devices: CE-60-DRY OVENSIFRAY FILTERS Release Point Apportionment: EP-60-REAR CRADLE WAX COATING: 100.0% |
| • | | Additional Information: Max Design Rate Amount: 1, Max Design Rate Unit Code: HOURS, Raw Material Desc: WAX | | | |

PROCESS EMISSIONS